



DN (mm/inch)	L MIN (inch)	L MAX (inch)	Threaded Rods (inch)	No. Rods (pcs)	A (inch)	B (inch)
80/3"	8.27	11.42	5/8	2	16.93	2.76
100/4"	8.27	11.42	5/8	2	16.93	2.76
125/5"	8.27	11.42	3/4	4	16.93	2.76
150/6"	8.27	11.42	3/4	4	16.93	2.76
200/8"	11.02	16.14	3/4	4	22.44	3.15
250/10"	11.02	16.14	7/8	4	22.44	3.15

- 1) Hyjoint 2001 meets or exceeds all specifications of AWWA Standard C219.
- 2) Center Ring - ASTM A 53 Grade A steel.
- 3) End Rings - ASTM A 795 steel.
- 4) Gaskets - EPDM compounded for water and sewerage, meets NSF 61 requirements.
- 5) Bolts and Nuts on the End Ring - Type 304 stainless steel.
Rolled thread and anti galling coating.
- 6) Bridge - Type 304 stainless steel.
- 7) Coating - 100% Fusion bonded epoxy for enhanced corrosion protection.
Average thickness 14 Mil.
- 8) G = Min. Pipe Insertion of 1.75 inch
- 9) Working Pressure : 175 PSI
- 10) Flange - meets AWWA class D.

				Part Name: DISMANTLING JOINT with FLANGE AWWA-D		KRAUSZ
Material		Weight		Note		
				Day	Name	Catalog No.
				Drawn	07.10.07 S.LORA	
				Check		Drawing No.
Edition	Change	Day	Name	Appr		811-56
						Scale