



- 1) Hymax 2000 meets or exceeds all specifications of AWWA Standard C219.
- 2) Center Ring - ASTM A 53 Grade A steel.
- 3) End Rings - ASTM A 795 steel.
- 4) Gaskets - EPDM compounded for water and sewerage, meets NSF 61 requirements.
- 5) Bolts and Nuts - Type 304 stainless steel. Rolled thread and anti galling coating.
- 6) Bridge - Type 304 stainless steel.
- 7) Coating -100% Fusion bonded epoxy for enhanced corrosion protection. Average thickness 14 Mil.
- 8) G = Min. Pipe Insertion of 2.25 inch.
- 9) Working Pressure :
 260 PSI for HYMAX 14" - 16"
 232 PSI for HYMAX 18" - 24".

ND (mm/inch)	Overall Range (inch)	Before removal the inner layer (inch)	After removal the inner layer (inch)	D (inch)	L (inch)	i (inch)	d (mm)	Approx. Weigth (Lbs)
350/14"	15.00-17.10	15.00-16.10	16.02-17.10	Ø21.00	11.6	8.0	M16	78
400/16"	17.10-19.20	17.10-18.19	18.11-19.20	Ø23.15	11.6	8.0	M16	88
450/18"	19.50-21.60	19.50-20.59	20.51-21.60	Ø25.55	11.6	8.0	M16	95
500/20"	21.50-23.60	21.50-22.60	22.52-23.60	Ø27.56	11.6	8.0	M16	101
600/24"	23.85-25.95	23.85-24.96	24.88-25.95	Ø29.13	11.6	8.0	M16	114
600/24" o.s.	24.60-26.70	24.60-25.67	25.59-26.70	Ø30.63	11.6	8.0	M16	114

			Part Name: Hymax 2000 with Cathodic Protection		KRAUSZ
Material	Weight	Note	Catalog No.		
		Day Name	Drawn 30/04/06	Oleg	Drawing No.
Edition	Change	Day Name	Check		
			Appr		
					Scale