



ND (mm/inch)	Overall Range (inch)	Before removal the inner layer (inch)	After removal the inner layer (inch)	D (inch)	L (inch)	i (inch)	d (mm)	Approx. Weight (Lbs)
40/1.5"	1.61-2.13	1.61-1.97	1.96-2.13	Ø3.94	6.1	3.9	M12	5
50/2"	2.10-3.03	2.10-2.60	2.56-3.03	Ø5.24	6.7	3.9	M12	6
80/3"	3.46-4.33	3.46-3.90	3.86-4.33	Ø6.69	8.7	5.9	M12	7
100/4"w	4.25-5.63	4.25-5.00	4.92-5.63	Ø8.66	8.8	5.9	M14	13
125/5"	5.12-6.38	5.12-5.75	5.71-6.38	Ø9.45	10.8	8.0	M14	17
150/6"	6.42-7.68	6.42-7.05	7.01-7.68	Ø10.75	10.8	8.0	M14	20
175/7"	7.48-8.74	7.48-8.11	8.07-8.74	Ø11.73	10.8	8.0	M14	25
200/8"	8.54-9.84	8.54-9.17	9.13-9.84	Ø12.91	10.8	8.0	M14	26
250/10"	10.70-12.00	10.70-11.37	11.33-12.00	Ø15.04	10.8	8.0	M14	28
250/10"o.s.	10.96-12.26	10.96-11.63	11.59-12.26	Ø15.28	10.8	8.0	M14	28
300/12"	12.40-13.66	12.40-13.03	12.99-13.66	Ø16.61	10.8	8.0	M14	31
300/12"o.s.	13.15-14.41	13.15-13.78	13.74-14.41	Ø17.32	10.8	8.0	M14	39

- 1) Hymax 2000 meets or exceeds all specifications of AWWA Standard C219.
- 2) Center Ring - ASTM A 53 Grade A steel.
- 3) End Rings - ASTM A 795 steel.
- 4) Gaskets - EPDM compounded for water and sewerage, meets NSF 61 requirements.
- 5) Bolts and Nuts - Type 304 stainless steel. Rolled thread and anti galling coating.
- 6) Bridge - Type 304 stainless steel.
- 7) Coating -100% Fusion bonded epoxy for enhanced corrosion protection. Average thickness 14 Mil.
- 8) G = Min. Pipe Insertion of 2.25 inch.
- 9) Working Pressure : 260 PSI.

		Part Name: Hymax 2000 with Cathodic Protection		KRAUSZ
Material	Weight	Note		
		Day	Name	Catalog No.
		Drawn	30/04/06	Oleg
Edition	Change	Day	Name	Drawing No.
		Appr		
				Scale