



- 1) Hyjoint 2001 meets or exceeds all specifications of AWWA Standard C219.
- 2) Center Ring – ASTM A 53 Grade A steel.
- 3) End Rings – ASTM A 795 steel.
- 4) Gaskets – NBR compounded.
- 5) Bolts & Nuts – Type 304 stainless steel. Rolled thread and anti galling coating.
- 6) Bridge – Type 304 stainless steel.
- 7) Coating – 100% Fusion bonded epoxy for enhanced corrosion protection.
Average thickness 14 Mil.
- 8) G = Min. Pipe Insertion of 1.75 inch

Material	Weight	Note	Part Name:	Scale
			HYJOINT 2001	
E		Day Name	Catalog No.	Project.
		Drawn 01.03.11 S.LORA		Project.
		Check	Drawing No.	Sheet
		Appr	801-56-XXXX-16A	1 of 2

Confidential Information. All rights reserved to Krausz Industries Ltd.
This document may not be copied, reproduced, displayed, modified or used in any way, whether in whole or in part, without the express prior written consent of Krausz Industries Ltd.



KRAUSZ

DN (inch)	Overall Range (inch)	D (inch)	L (inch)	No.-d (mm)	Torque (Ft-Lbs)	Working Pressure liquid (PSI)	Working Pressure nitrogen (PSI)	Vacuum (PSI)	Approx. Weight (Lbs)
12"	12.68-12.89	Ø15.1	8.19	4-M14	65	260	175	-12	28
14"	13.90-14.11	Ø16.2	8.19	4-M14	65	232	175	-12	30
16"	15.91-16.12	Ø18.2	8.19	4-M14	80	232	175	-12	33
18"	17.91-18.13	Ø20.2	10.35	4-M14	80	232	175	-12	51
20"	19.92-20.14	Ø22.2	10.35	4-M14	80	232	175	-12	58
24"	23.94-24.15	Ø26.2	10.35	4-M14	100	232	175	-12	112

Material		Weight		Note		Part Name: HYJOINT 2001		Scale	
E				Drawn	01.03.11	S.LORA	Catalog No.	Project:	
Change	Day	Name	Check	Appr			Drawing No.	Sheet	
							801-56-XXXX-16A	2 of 2	

Confidential Information. All rights reserved to Krausz Industries Ltd.
This document may not be copied, reproduced, displayed, modified or used
in any way, whether in whole or in part, without the express prior written
consent of Krausz Industries Ltd.

