

# **TPS** Total Piping Solutions, Inc.

*Product Selection Guide for Water, Wastewater and Industry*

## **Wide Range Pipe Joining**

<i>Hymax 2000 Standard Diameter</i>	<i>1.5 to 12"</i>	
<i>Hymax 2000 Large Diameter</i>	<i>14 to 24"</i>	
<i>Hymax 2000 Long Body Couplings</i>	<i>3 to 24"</i>	
<i>Hymax 2100 Flanged Adaptors</i>	<i>3 to 24"</i>	
<i>Hymax 2100 Long Body Flanged Adaptors</i>	<i>3 to 12"</i>	
<i>Hymax 2100 Flanged Meter Adaptors</i>	<i>1.5 to 2"</i>	
<i>Hymax 2200 Reducers</i>	<i>2x3 to 20x24"</i>	

*For Specific Information Regarding Application of Products, Please Consult with Factory*



## ***Dedicated Fit Pipe Joining***

***HyJoint Coupling***

***2 to 24"***



***Series 6000 Compression Fitting  
for IP or with copper adaptor***

***1/2 to 2"***



***Series 6100 Male Adaptors  
for IP Connections***

***1/2 to 2"***



## ***Pipe Repair Clamps***

***EZ-MAX Plus 4000***

***1.5 to 12"***



***Hydroflex 3000***

***14 to 50"***



***Quick Clamp 4100***

***1/2 to 6"***



## ***Products for Tapping Pipe (for Service Renewal and Primary Tapping)***

***EZ-MAX Plus with Tap  
(Tap sizes from 1/2 to 2")***

***3 to 12"***



***Tap Max Plus Service Saddle  
(for tapping PVC or Ductile, fully insulated 9" widths only)***

***3 to 12"***

## ***Specialty Pipe Joining***

***Dismantling Joint***

***3 to 24"***



***Total Piping Solutions, Inc.  
1760 Haskell Road, Olean, New York 14760  
Tel: 716-372-0160 Fax: 716-372-1767***

***Email: [sales@tps.us](mailto:sales@tps.us)  
Website: [www.tps.us](http://www.tps.us)***

***PSG 08/07***