

Meets the New AWWA C-230 Standard

EZ-MAX[®] Plus *Repair Clamp*

EZ-MAX[®] Plus with Taps



Total Piping Solutions, Inc.

®

EZ-MAX[®] PLUS Repair Clamp

EZ-MAX[®] PLUS 4000 Series Pipe Repair Clamps

The EZ-MAX PLUS 4000 repair clamp is suited to a wide range of pipe repair conditions, and each size will replace between three and four standard range clamp designs in your inventory.

Each repair clamp accommodates a range of up to 8/10ths of an inch. The EZ-MAX repair clamp is available in widths ranging from 6", 9", 12", 15" and 24" wide.

The EZ-MAX PLUS 4000 offers an efficient range adjustable band, a deep waffled mat-type gasket with pressure-assisted sealing rings and NSF61 Registered EPDM compounded gasket. The gasket is equipped with a spanner plate that is mechanically attached to the band to provide completely uniform gasket pressure. This method eliminates the need to mold the spanner plate in the gasket, allowing the EZ-MAX to provide a faster seal during installation.

The EZ-MAX PLUS 4000 wraparound clamp requires no disassembly. The installer simply wraps the clamp around the pipe, slides it over the break, applies the quick-set lug system and tightens the bolts to the required torque. All work is performed from the topside of the low profile clamp, eliminating the need for extra excavation and under-dig for the wrench.

The EZ-MAX PLUS 4000 can be easily handled by one person due to the nature of its superior lightweight materials of construction. The repair clamp is equipped with a corrosion-resistant type 304 stainless steel pipe-reinforcing band, and comes with 304 stainless steel spanner, nuts and bolts.



Tapped Outlets for Versatility

- Taps available in all EZ-MAX Plus Clamps
- ½ to 2 Inch Diameter Outlets
- EZ-MAX Plus sold as a saddle in 9” widths
- Superior *Proprietary TIG weld attachment method.*
- AWS Certified Weld Processes
- All Welds fully *Passivated*
- AWWA Threads (Corporation Cock “CC” threading)
- National Pipe Threads
- *Double “O” Ring Seal* at the branch
- Built tough for durability and a life time of service
- *150 PSI* Rated working pressure
- Standard double “O” Ring branch gasket for taps on Ductile Iron, Cast Iron, Steel, PVC, Polyethylene
- All Clamps Equipped with Service Outlets Meet or Exceed ANSI/AWWA C-800-07 entitled “Underground Service Line Valves and Fittings”



Total Piping Solutions, Inc.

1760 Haskell Road
Olean, New York 14760

TEL: 716-372-0160

FAX: 716-372-1767

E-Mail: sales@tps.us



VISIT OUR WEBSITE: <http://tps.us>


Form EZ-MAX/TAPS 5/11

Krausz



Patented and Trademarked by *Krausz Industries, Ltd.*

	WARNING	This product is not intended for use on natural gas piping or any other type of gas piping. To do so could result in escaping gas that could ignite and cause property damage, serious injury or death.
		

	WARNING	This is a non-restraining product. If pipe pullout can occur, proper anchoring of the pipe joint is required. Failure to anchor the pipe could result in the escape of line content, and may cause property damage, serious injury or death.
